

09/581264

PROCESS FOR THE DETERMINATION OF MTBE IN THE GROUND AND
AIR.

The present invention relates to a process for the determination of pollution by methyl ter butyl ether.

5 Methyl ter butyl ether (MTBE) is the most widely used among oxygenated additives for motor vehicles. Its addition improves combustion and significantly reduces the emission of carbon monoxide, especially during low winter temperatures. The possibility of a
10 leakage in the earth of fuels contained in underground tanks of service stations is probable. As a result of this, MTBE has been the object of a great deal of research with respect to its destiny in the environment and its potential impact on public health, mainly
15 bearing in mind that this substance is extremely volatile and soluble in water. In addition, if present, it remains in deep water and sediments as owing to its very limited biodegradability, with an odour that can be noticed starting from concentrations at a level of

20 ppb. Its cancerogenous activity, if existing, seems to be small.

There are various methods for determining and measuring MTBE: they range from gas chromatography to
5 IRA and flame-ionization, but they are all difficult to apply to the ground.

We have now overcome these problems by means of a process which allows the continuous monitoring of MTBE, in the ground and on the surface, using sensors in the
10 solid state.

In accordance with this, the present invention relates to a process for monitoring methyl ter butyl ether (MTBE) vapours, in concentrations equal to or higher than 0.1 ppm, in the ground and overlying
15 atmosphere comprising:

- a) adopting a series of MTBE vapour sensors of which at least one in the earth, equipped with a membrane permeable to gases and impermeable to water, and at least one in the air on the surface of the ground,
20 these sensors consisting of
- a sensitive element made of a semi-conductor metal oxide containing platinum;
 - a heater capable of bringing the temperature of said sensitive element to a range of 300 and 500°C;
- 25 b) - continuously observing the resistance variations

of the sensitive elements by interaction with MTBE,
- comparing the signals emitted by the sensor in the
earth and the sensor in the air on the ground-surface;
- evaluating on the basis of this comparison the
5 presence and concentration of MTBE in the surface
layers or depths of the ground and in the atmosphere
above the ground itself.

A further object of the present invention relates
to the device for effecting the process.

10 A typical embodiment of the invention is described
hereunder, with reference to figures 1 and 2 in which
equal numbers correspond to equal elements.

Figure 1 illustrates a sensor, in enlarged form.
The sensitive element 1 is produced by placing by
15 . screen printing, on an aluminum slab with dimen-
sions of 3 x 9 x 0.25 mm, a 40 micron layer of a tin
oxide paste, containing platinum. Powders are used
having a particle size of less than 1 micron containing
from 20 to 30% by weight of alumina and organometallic
20 platinum as catalyst in a quantity ranging from 0.1 to
1% by weight. A resistor (consisting of a layer of any
commercial screen printing conductor paste capable of
resisting at least 400°C) is deposited, again by
screen printing, on the opposite side of the slab,
25 to keep the sensitive element at an operating tempera-

ture of 300-500°C. After depositing the electric contacts also by screen printing, the slab is subjected to a baking step in an oven at 800-1000°C for an hour.

5 Finally the device, which forms the sensitive element, is assembled on a T078 2 container and inserted in a steel cylinder 3 closed by means of a flame-shield net 4. If the sensor described is fixed into the ground, a membrane 5, permeable to gases and imperme-
10 able to water, is inserted under the flame-shield net to prevent any possible water present in the earth from entering into contact with the sensitive element. An appropriate porous septum or even better a membrane made of ePFTE material can be used for the purpose.

15 The sensitive elements can alternatively be produced with other types of semi-conductor metal oxides, but still using platinum as catalyst.

The sensors are equipped with feeders, or alternatively batteries, to supply energy to the heater and
20 resistivity measurement circuit of the sensitive element.

Figure 2 illustrates an underground tank 6 of a service station for leadless fuels with a configuration with three sensors for the embodiment of the present
25 invention. Two sensors 7, like those described with a

gas permeable membrane, are fixed in the ground at the sides of the tank, a sensor 8 without a membrane inserted in the chamber 9 above the tank. 10 illustrates the data acquisition switchboard.

5 Sensors such as those described above have a sensitivity which is such as to signal the presence of vapours of gasoline containing MTBE or MTBE alone with concentrations even less than 1 ppm in the air. The possibility of comparing the signals coming from the
10 sensors fixed in the ground with those situated in the chamber above the tank over a period of time, make it possible to distinguish between leakages on the ground surface and losses from the underground tank.

 In another embodiment of the same invention,
15 sensors can be placed along an underground pipe around it and on the ground surface above. In this case the signals emitted from the sensors can be sent via radio to a central unit for collection and processing.

 A few examples are provided below for a better
20 understanding of the present invention but should not be considered as limiting the scope of the invention itself.

EXAMPLE 1

 Using a sensor according to the one described
25 above, and a tin container, conductivity measurements

are carried out in the presence of gasoline vapours to which 10% of MTBE has been added.

In figure 3.(a) the trace shows the kinetics response of the sensor in relation to the time at various concentrations of gasoline.

Figure 3.(b) shows the variation in the resistance in relation to the concentrations of gasoline. As can be seen the response is proportional to the concentration logarithm and allows concentrations of less than 1 ppm to be detected.

EXAMPLE 2

With the procedure described above, a system consisting of two MTBE sensors and an electronic control unit is prepared.

One of the sensors, protected by an ePFTE membrane, is inserted, up to a depth of about 10 cm, in a tank of 50 x 40 x 30 cm full of sandy earth. The second sensor is placed at about 20 cm from the first and about 5 cm from the surface.

After a stabilization period of about 30 minutes 1 ml of gasoline containing 10% of MTBE is injected with a syringe into the ground, at a distance of 10 cm from the underground sensor and at a depth of 10 cm. In figure 4 the temporal point of the injection is indicated with the arrow A. As can be observed, the trace

registered by the sensor in the air (2) indicates an almost immediate decrease in resistance, whereas the trace registered by the sensor in the ground (1) indicates a delay of about 5 min. before the decrease
5 in resistance.

After a few hours, 1 ml of gasoline (indicated with the arrow B in figure 4B) is injected again. As can be observed, the trace of the sensor in the ground (1) begins to indicate a decrease in resistance start-
10 ing from the level reached with the previous injection of gasoline. This shows that the sensor is capable of monitoring a further leakage also starting from ground which has already been polluted.

With respect to the trace in air, this starts from
15 a much higher resistance value of the sensor as gasoline vapours dilute very rapidly in air, unlike the ground where the vapours interstitial tend to remain trapped.

The time delay of a few minutes in this case, shown by the response of the sensor fixed in the ground
20 with respect to that in the air depends on the fact that in the earth interstitial vapours of gasoline and MTBE, although being mobile enough to allow this type of measurement, need a certain amount of time to spread from the leakage point to the sensor. In air the
25 vapours obviously spread at a much faster rate and the

sensor consequently does not show significant delays.

As mentioned in the description, the different behaviour of sensors in the ground and in the air enables a leakage in the surface to be distinguished

5 from a leakage in depth in the ground.

57th 4th 1st 2nd 3rd 4th 5th 6th 7th 8th 9th 10th 11th 12th 13th 14th 15th 16th 17th 18th 19th 20th 21st 22nd 23rd 24th 25th 26th 27th 28th 29th 30th 31st 32nd 33rd 34th 35th 36th 37th 38th 39th 40th 41st 42nd 43rd 44th 45th 46th 47th 48th 49th 50th 51st 52nd 53rd 54th 55th 56th 57th 58th 59th 60th 61st 62nd 63rd 64th 65th 66th 67th 68th 69th 70th 71st 72nd 73rd 74th 75th 76th 77th 78th 79th 80th 81st 82nd 83rd 84th 85th 86th 87th 88th 89th 90th 91st 92nd 93rd 94th 95th 96th 97th 98th 99th 100th 101st 102nd 103rd 104th 105th 106th 107th 108th 109th 110th 111th 112th 113th 114th 115th 116th 117th 118th 119th 120th 121st 122nd 123rd 124th 125th 126th 127th 128th 129th 130th 131st 132nd 133rd 134th 135th 136th 137th 138th 139th 140th 141st 142nd 143rd 144th 145th 146th 147th 148th 149th 150th 151st 152nd 153rd 154th 155th 156th 157th 158th 159th 160th 161st 162nd 163rd 164th 165th 166th 167th 168th 169th 170th 171st 172nd 173rd 174th 175th 176th 177th 178th 179th 180th 181st 182nd 183rd 184th 185th 186th 187th 188th 189th 190th 191st 192nd 193rd 194th 195th 196th 197th 198th 199th 200th 201st 202nd 203rd 204th 205th 206th 207th 208th 209th 210th 211st 212nd 213th 214th 215th 216th 217th 218th 219th 220th 221st 222nd 223rd 224th 225th 226th 227th 228th 229th 230th 231st 232nd 233rd 234th 235th 236th 237th 238th 239th 240th 241st 242nd 243rd 244th 245th 246th 247th 248th 249th 250th 251st 252nd 253rd 254th 255th 256th 257th 258th 259th 260th 261st 262nd 263rd 264th 265th 266th 267th 268th 269th 270th 271st 272nd 273rd 274th 275th 276th 277th 278th 279th 280th 281st 282nd 283rd 284th 285th 286th 287th 288th 289th 290th 291st 292nd 293rd 294th 295th 296th 297th 298th 299th 300th 301st 302nd 303rd 304th 305th 306th 307th 308th 309th 310th 311st 312nd 313th 314th 315th 316th 317th 318th 319th 320th 321st 322nd 323rd 324th 325th 326th 327th 328th 329th 330th 331st 332nd 333rd 334th 335th 336th 337th 338th 339th 340th 341st 342nd 343rd 344th 345th 346th 347th 348th 349th 350th 351st 352nd 353rd 354th 355th 356th 357th 358th 359th 360th 361st 362nd 363rd 364th 365th 366th 367th 368th 369th 370th 371st 372nd 373rd 374th 375th 376th 377th 378th 379th 380th 381st 382nd 383rd 384th 385th 386th 387th 388th 389th 390th 391st 392nd 393rd 394th 395th 396th 397th 398th 399th 400th 401st 402nd 403rd 404th 405th 406th 407th 408th 409th 410th 411st 412nd 413th 414th 415th 416th 417th 418th 419th 420th 421st 422nd 423rd 424th 425th 426th 427th 428th 429th 430th 431st 432nd 433rd 434th 435th 436th 437th 438th 439th 440th 441st 442nd 443rd 444th 445th 446th 447th 448th 449th 450th 451st 452nd 453rd 454th 455th 456th 457th 458th 459th 460th 461st 462nd 463rd 464th 465th 466th 467th 468th 469th 470th 471st 472nd 473rd 474th 475th 476th 477th 478th 479th 480th 481st 482nd 483rd 484th 485th 486th 487th 488th 489th 490th 491st 492nd 493rd 494th 495th 496th 497th 498th 499th 500th 501st 502nd 503rd 504th 505th 506th 507th 508th 509th 510th 511st 512nd 513th 514th 515th 516th 517th 518th 519th 520th 521st 522nd 523rd 524th 525th 526th 527th 528th 529th 530th 531st 532nd 533rd 534th 535th 536th 537th 538th 539th 540th 541st 542nd 543rd 544th 545th 546th 547th 548th 549th 550th 551st 552nd 553rd 554th 555th 556th 557th 558th 559th 560th 561st 562nd 563rd 564th 565th 566th 567th 568th 569th 570th 571st 572nd 573rd 574th 575th 576th 577th 578th 579th 580th 581st 582nd 583rd 584th 585th 586th 587th 588th 589th 590th 591st 592nd 593rd 594th 595th 596th 597th 598th 599th 600th 601st 602nd 603rd 604th 605th 606th 607th 608th 609th 610th 611st 612nd 613th 614th 615th 616th 617th 618th 619th 620th 621st 622nd 623rd 624th 625th 626th 627th 628th 629th 630th 631st 632nd 633rd 634th 635th 636th 637th 638th 639th 640th 641st 642nd 643rd 644th 645th 646th 647th 648th 649th 650th 651st 652nd 653rd 654th 655th 656th 657th 658th 659th 660th 661st 662nd 663rd 664th 665th 666th 667th 668th 669th 670th 671st 672nd 673rd 674th 675th 676th 677th 678th 679th 680th 681st 682nd 683rd 684th 685th 686th 687th 688th 689th 690th 691st 692nd 693rd 694th 695th 696th 697th 698th 699th 700th 701st 702nd 703rd 704th 705th 706th 707th 708th 709th 710th 711st 712nd 713th 714th 715th 716th 717th 718th 719th 720th 721st 722nd 723rd 724th 725th 726th 727th 728th 729th 730th 731st 732nd 733rd 734th 735th 736th 737th 738th 739th 740th 741st 742nd 743rd 744th 745th 746th 747th 748th 749th 750th 751st 752nd 753rd 754th 755th 756th 757th 758th 759th 760th 761st 762nd 763rd 764th 765th 766th 767th 768th 769th 770th 771st 772nd 773rd 774th 775th 776th 777th 778th 779th 780th 781st 782nd 783rd 784th 785th 786th 787th 788th 789th 790th 791st 792nd 793rd 794th 795th 796th 797th 798th 799th 800th 801st 802nd 803rd 804th 805th 806th 807th 808th 809th 810th 811st 812nd 813th 814th 815th 816th 817th 818th 819th 820th 821st 822nd 823rd 824th 825th 826th 827th 828th 829th 830th 831st 832nd 833rd 834th 835th 836th 837th 838th 83